

100 M Connection | Keeps data even out of range | 16 hours operation time

The MS836B laser scanner features mobility 2.4G wireless technology and accurate linear scanning performance that gives your business flexibility and freedom. The well-integrated mobility design allows users to move around without being restricted, while supporting high comfort over long periods of operation. This device enhances the workflow efficiency in an affordable price for a wide range of market applications, such as point-of-sale, inventory control, and warehouse management.

Move without Restrictions

Design for mobile workers, the MS836B comes with a USB dongle that enables users to capture barcodes with freedom wireless connection. Easy plug-and-play function, the MS836B pairs easily to laptops or PCs without complicated set-up. Besides, it allows users to transmit data to the host from up to 100 meters from the base via 2.4G wireless communication. When it is out of range, the MS836B barcode scanner can store 40,000 EAN codes in memory and upload them to your devices at your own convenience. It allows associates to capture barcodes from the checkout counter or checking your store's inventory in the retail store without restrictions.

Accurate Laser Scanning Performance

Quickly and accurate capturing most linear barcodes or coupon displayed on the phone, the MS836B helps staff to record inventory without any frustration. It is equipped with advanced high-speed engine that has ability to decode poor quality codes and achieve 100 times per second. It streamline everyday processes in supermarket, retail store and warehouse applications.

Durable Design

Furthermore, it has an IP42 rating for dust and water resistance as well as a 1.5 meter drop spec that provides superior durability and reliability. Combining high performance and compact design, M836B gives mobile worker conveniently and safely while on the go.

Features

- 2.4G wireless transmission range up to 100m in the line of open sight.
- Superior laser scanning: reads all major linear barcodes including printed and digital
- High-Speed data capture performance: up to 100 times/ sec
- Long battery life up to 30 hours per a fully charged battery
- Durable, Compact and Long life trigger designRugged design by IP42 and 1.5m drops
- Buffer mode for out-of-range reading
- Instant decoding feedback: LED, Buzzer indicators







MS836B Specifications

Optical & Performance

Sensor 1D Laser Engine

Aiming Element Laser

Ambient Light 0-100,000 Lux Scan Rate 100 times/ sec Skew Angle ±60° Memory 16MB

Optical Resolution ≥ 4mil (code 39)

Depth of Field 10mm-265mm(13 mil, EAN13, PCS=90%)

Communication

2.4G Wireless

Wireless Coverage 2.4G: 100M(line of sight)

2.4G: USB Interface/ Profile

Bluetooth: HID, BLE, SPP

Host Interface supported

Mechanical

Dimension 174mm \times 72mm \times 96mm (L \times W \times H)

216g Weight

Functionality

Operation Mode Trigger Mode, Presentation Mode, Buffer Mode

Regulatory Approvals

CE, FCC, BSMI, VCCI

Symbologies

1D Industoal 2 of 5, Standard 25, Matrix 25,

China post 25, Code 11, Codabar, MSI/plessey, UK/plessey, Code39

(Standard 39& Full ASCII Code 39)Code 32, Code 93, Code128, UPCA, UPCE, EAN13, EAN8, UPC/EAN add-on 2/5, ISBN, ISSN,

GS1(RSS)

RSS-14,LIMITED, EXPENDED, Include GS1

STACK

Data Formatting Prefix, Suffix, Code ID

Electrical

Indicator

Battery Type

Operation Voltage DC 5V

Current Consumption Operation mode: <120mA,

Standby mode: <85mA Buzzer LED light Lithium-ion

Battery Capacity 2600mAh 18650 battery Battery Charging time Fully charged in 5 hours Operating Time Over 30 hours

Environmental

Mechanical Shock 1.5m onto concrete (scanner only)

Operating Temperature -10°C to 50°C -20°C to 60°C Storage Temperature

Relative Humidity 5% to 90% non-condensing IP Rating

IP42

Package Contents

MS836B scanner 2.4G Dongle USB Charging Cable







Headquarters Taipei, Taiwan

http://www.ute.com e-mail: info@hq.ute.com

unitech America

Los Angeles

e-mail: info@us.ute.com http://us.ute.com http://can.ute.com info@can.ute.com

http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei

http://apac.ute.com info@apac.ute.com / info@india.ute.com

http://mideast.ute.com info@mideast.ute.com

unitech Europe Tilburg / Netherlands

http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan Tokyo

http://jp.ute.com e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com/info@cn.ute.com/ Taipei http://tw.ute.com info@tw.ute.com

