



# **MY PRINTER X**

# High-tech portable mini printer

MY PRINTER X is a high-tech portable mini printer. It is ultra-light and compact, with large paper roll (30mm diameter). High printing capacity thanks to its powerful batteries: approximately 30mt of printed paper! USB Interface or RS232 with special cable as optional. It comes with paper end sensor, supports an upgradable customer logo and prints the most used barcodes. Auto-installing drivers: Windows, Linux, Android and iOS. Thanks to the Bluetooth® technology, MY PRINTER X can print from Android, iOS. Practical belt hook, battery charger and USB cable included in the package.















#### **CHARACTERISTICS**

- Portable mini printer with Hi-tech design
- Ultra-light and compact: only 205g!
- Bluetooth® wireless technology and USB
- High performance: 10m printed paper
- International fonts on-board: any language available
- 1D and 2D (PDF417, QRCODE) barcodes printing
- RGB LED
- Paper thickness: 61⊠m
- Dimensions: 110mm (L) x85mm (D) x45mm (H)

#### **BATTERIES:**

- Battery: Li-Ion 7.4V 1500mAh, rechargeable
- Battery charger: 2A through USB cable
- Recharge cycle: 4.5 hours max.
- Performance and capacity: 30m paper; 100 hours in stand-by with Bluetooth® interface

#### **SOFTWARE:**

- CUSTOMPRINT
- CUSTOM PRINT SERVICE

### **ACCESSORIES**

Protective case











# **TECHNICAL SHEET**

Number of dots 8 dots / mm  Resolution 203 DPI  Printing (mm/sec) max 60 (this depends on the battery status, type of printing and environment temperature)  Character set PC437, PC850, PC860, PC863, PC865, PC858 (Euro)  Printing Format 1x to 8x height and width, reverse, underlined, script, bold  Printing Direction Straight, 90°, 180°, 270°  Paper width 57 mm  Paper weight from 55 to 60 g/m²  Paper thickness 61½m  Printing width 48 mm  Roll Dimension max Ø 33mm +/- 1 mm  Emulation CUSTOM / POS  Interfaces USB + Bluetooth or RS232 with special cable as optional  Data Buffer 2 KB  Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Power supply Input: from 100 Vac to 240 Vac Output: 5 ½ 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Printing Method	Thermal printing
Printing (mm/sec) max 60 (this depends on the battery status, type of printing and environment temperature)  Character set PC437, PC850, PC860, PC863, PC865, PC888 (Euro)  Printing Format 1x to 8x height and width, reverse, underlined, script, bold  Printing Direction Straight, 90°, 180°, 270°  Paper width 57 mm  Paper weight from 55 to 60 g/m²  Paper thickness 61\( \text{km} \)  Printing width 48 mm  Roll Dimension max \( \text{\Omega} \) 33mm +/- 1 mm  Emulation CUSTOM / POS  Interfaces USB + Bluetooth or RS232 with special cable as optional  Data Buffer 2 KB  Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Number of dots	8 dots / mm
Character set PC437, PC850, PC863, PC863, PC865, PC858 (Euro)  Printing Format 1x to 8x height and width, reverse, underlined, script, bold  Printing Direction Straight, 90°, 180°, 270°  Paper width 57 mm  Paper weight from 55 to 60 g/m²  Paper thickness 618m  Printing width 48 mm  Roll Dimension max Ø 33mm +/- 1 mm  Emulation CUSTOM / POS  Interfaces USB + Bluetooth or RS232 with special cable as optional  Data Buffer 2 kB  Flash Memory 512 kB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8, 1, 10(+32/64bit support), Linux(32/64 bit support), Android and IOS  Software Tools FontMake, LogoMake, UpgCePrn  Power supply Input: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Resolution	203 DPI
Printing Format  1x to 8x height and width, reverse, underlined, script, bold  Printing Direction  Straight, 90°, 180°, 270°  Paper width  57 mm  Paper weight  from 55 to 60 g/m²  Paper thickness  618m  Printing width  48 mm  Roll Dimension  max Ø 33mm +/- 1 mm  Emulation  CUSTOM / POS  Interfaces  USB + Bluetooth or RS232 with special cable as optional  Data Buffer  2 KB  Flash Memory  512 KB  Supported Bluetooth Profile  SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers  Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and IOS  Software Tools  FontMake, LogoMake, UpgCePrn  Power supply  Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption  500mA (12,5% printing rate)  Operating temperature  -20°C + 70°C  Safety  EN60950 2001  Marks  Bluetooth, CE, RoHS compliant  Dimensions  110 (L) x 45 (H) x 85 (W) mm	Printing (mm/sec)	max 60 (this depends on the battery status, type of printing and environment temperature)
Printing Direction  Straight, 90°, 180°, 270°  Paper width  57 mm  Paper weight  from 55 to 60 g/m²  Paper thickness  61 m  Printing width  48 mm  Roll Dimension  max Ø 33mm +/- 1 mm  Emulation  CUSTOM / POS  Interfaces  USB + Bluetooth or RS232 with special cable as optional  Data Buffer  2 KB  Flash Memory  512 KB  Supported Bluetooth Profile  SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers  Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools  FontMake, LogoMake, UpgCePrn  Power supply  Input: from 100 Vac to 240 Vac Output: 5 ½± 10%  Medium consumption  500mA (12,5% printing rate)  Operating temperature  -20°C + 70°C  Safety  EN60950 2001  Marks  Bluetooth, CE, RoHS compliant  Dimensions  110 (L) x 45 (H) x 85 (W) mm	Character set	PC437, PC850, PC860, PC863, PC865, PC858 (Euro)
Paper width 57 mm  Paper weight from 55 to 60 g/m²  Paper thickness 61\( \text{Im} \)  Printing width 48 mm  Roll Dimension max \( \text{Ø 33mm +/- 1 mm} \)  Emulation CUSTOM / POS  Interfaces USB + Bluetooth or RS232 with special cable as optional  Data Buffer 2 KB  Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Printing Format	1x to 8x height and width, reverse, underlined, script, bold
Paper weight from 55 to 60 g/m²  Paper thickness 61\( \text{\text{Mm}} \)  Printing width 48 mm  Roll Dimension max \( \text{\text{9}} \) 33mm +/- 1 mm  Emulation CUSTOM / POS  Interfaces USB + Bluetooth or RS232 with special cable as optional  Data Buffer 2 KB  Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Power supply Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Printing Direction	Straight, 90°, 180°, 270°
Paper thickness 61\( \text{Im} \)  Printing width 48 mm  Roll Dimension max \( \text{\text{0}} \) 33mm +/- 1 mm  Emulation CUSTOM / POS  Interfaces USB + Bluetooth or RS232 with special cable as optional  Data Buffer 2 KB  Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Power supply Input: from 100 Vac to 240 Vac	Paper width	57 mm
Printing width 48 mm  Roll Dimension max Ø 33mm +/- 1 mm  Emulation CUSTOM / POS  Interfaces USB + Bluetooth or RS232 with special cable as optional  Data Buffer 2 KB  Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Power supply Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Paper weight	from 55 to 60 g/m²
Roll Dimension max Ø 33mm +/- 1 mm  Emulation CUSTOM / POS  Interfaces USB + Bluetooth or RS232 with special cable as optional  Data Buffer 2 KB  Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Power supply Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Paper thickness	61⊠m
Emulation CUSTOM / POS  Interfaces USB + Bluetooth or RS232 with special cable as optional  Data Buffer 2 KB  Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Power supply Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Printing width	48 mm
Interfaces  USB + Bluetooth or RS232 with special cable as optional  Data Buffer  2 KB  Flash Memory  512 KB  Supported Bluetooth Profile  SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers  Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools  FontMake, LogoMake, UpgCePrn  Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption  500mA (12,5% printing rate)  Operating temperature  -20°C + 70°C  Safety  EN60950 2001  Marks  Bluetooth, CE, RoHS compliant  Dimensions  110 (L) x 45 (H) x 85 (W) mm	Roll Dimension	max Ø 33mm +/- 1 mm
Data Buffer 2 KB  Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Power supply Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Emulation	CUSTOM / POS
Flash Memory 512 KB  Supported Bluetooth Profile SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools FontMake, LogoMake, UpgCePrn  Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Interfaces	USB + Bluetooth or RS232 with special cable as optional
Supported Bluetooth Profile  SPP (Serial Port Profile), OPP (Object Push Profile)  Drivers  Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools  FontMake, LogoMake, UpgCePrn  Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption  500mA (12,5% printing rate)  Operating temperature  -20°C + 70°C  Safety  EN60950 2001  Marks  Bluetooth, CE, RoHS compliant  Dimensions  110 (L) x 45 (H) x 85 (W) mm	Data Buffer	2 KB
Drivers  Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS  Software Tools  FontMake, LogoMake, UpgCePrn  Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption  500mA (12,5% printing rate)  Operating temperature  -20°C + 70°C  Safety  EN60950 2001  Marks  Bluetooth, CE, RoHS compliant  Dimensions  110 (L) x 45 (H) x 85 (W) mm	Flash Memory	512 KB
Software Tools FontMake, LogoMake, UpgCePrn  Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Supported Bluetooth Profile	SPP (Serial Port Profile), OPP (Object Push Profile)
Power supply  Input: from 100 Vac to 240 Vac Output: 5 V± 10%  Medium consumption  500mA (12,5% printing rate)  Operating temperature  -20°C + 70°C  Safety  EN60950 2001  Marks  Bluetooth, CE, RoHS compliant  Dimensions  110 (L) x 45 (H) x 85 (W) mm	Drivers	Windows 7, 8, 8.1, 10(+32/64bit support), Linux(32/64 bit support), Android and iOS
Power supply Output: 5 V± 10%  Medium consumption 500mA (12,5% printing rate)  Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Software Tools	FontMake, LogoMake, UpgCePrn
Operating temperature -20°C + 70°C  Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Power supply	·
Safety EN60950 2001  Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Medium consumption	500mA (12,5% printing rate)
Marks Bluetooth, CE, RoHS compliant  Dimensions 110 (L) x 45 (H) x 85 (W) mm	Operating temperature	-20°C + 70°C
Dimensions 110 (L) x 45 (H) x 85 (W) mm	Safety	EN60950 2001
	Marks	Bluetooth, CE, RoHS compliant
Weight 205 gr	Dimensions	110 (L) x 45 (H) x 85 (W) mm
200 61	Weight	205 gr

# **MODELS**



911CP010300A33 MOBILE PRINTER MY PRINTER X









CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: TI80WI0

The technical data on this website are not binding and may be changed without advanced notice. Last update: 22 January 2020





