



# 1723L 17-inch LCD

Touchscreen Monitor



**Integrated Touch**



**Commercial Grade**



**3-Year Warranty**

## Product Overview

The Elo 1723L 17-inch standard format touchscreen monitor meets the durability and aesthetic requirements for a variety of high traffic retail and hospitality interactive solutions. The sleek, edge-to-edge glass design of the 1723L brings a clean, modern feel to any environment. The zero-bezel monitor is available in both black or white with Elo's industry-leading touch technologies, both providing a stable drift-free operation with outstanding image clarity, resolution and light transmission - for an accurate touch response and vivid images.

The 1723L has been designed for touch from the ground up, with such features as a spill-resistant sealing, adjustable height stand with tilting functionality, VESA mounting option, connectivity incorporated within the monitor (reducing the number of power bricks), and communication cables and side controls with lockout capability.

### Available touch technologies:

- IntelliTouch® SAW
- TouchPro® PCAP

**Customize with an integrated 3-track magnetic stripe reader (MSR)**

**Integrated cable management**

## 1723L 17-inch LCD Touchscreen Monitor

Specifications	
Model	1723L
Color	Black or white
Active Display Area	13.3" x 10.64" (337.92mm x 270.34mm)
Dimensions	15.43" x 8.24" x 14.20" (391.9mm x 209.4mm x 360.7mm)
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	17"
Aspect Ratio	5:4
Native Resolution	1280 x 1024
Preset Video Timings	640 x 480 60Hz, 75Hz; 720 x 400 70Hz; 800 x 600 56Hz, 60Hz, 75Hz; 1024 x 768 60Hz, 75Hz; 1280 x 1024 60Hz, 75Hz
Number Of Colors	16.7 million
Number of Touches	Dual-touch and multi-touch
Brightness (Typical)	LCD Panel: 250 nits; TouchPro PCAP: 215 nits; IntelliTouch ZB: 225 nits
Response Time (Tr + Tf) (Typical)	5 msec
Viewing Angle (Typical)	Horizontal: ±85° or 170° total / Vertical: ±80° or 160° total
Contrast Ratio (Typical)	1000:1
Video	Analog VGA on Female DB-15 connector; Digital DVI on Female DVI-D, Dual-Link connector; Input Video Horizontal Sync frequency range: 31.5-80KHz; Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Speakers	2 x 2W internal speakers
Additional Ports	2 External USB Ports
Power	Monitor input power connector: Coaxial power jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC ±5% (Note: This monitor is sold with an AC-DC power adapter.); Adapter input connector: IEC 60320 C14; Adapter input voltage range: 100-240VAC, 50/60Hz; Power Consumption (monitor + AC/DC adapter - Typical) - ON: 19.2W; SLEEP: 3.0W; OFF: 0.19W
On-Screen Display (OSD)	Accessible through switches along the bottom. Controls: Menu, Up, Down, Select; Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Volume, Mute, Recall Defaults; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power
Mounting Options	VESA 4-hole 75mm mounting interface on rear of unit; 3-hole threaded mounting on bottom of stand
Weight	Unpackaged: 11.46 lbs (5.2 kg); Packaged: 18.7 lbs (8.5 kg)
Shipping Dimensions	19.65" x 17.17" x 8.39" (499mm x 436mm x 213mm)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 140°F (-20°C to 60°C)
Humidity (Non-Condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory Approvals and Declarations	C-Tick; cUL, IC; CCC; CE; VCCI; KCC, e-Standby; CoC; BSMI Mark; UL, FCC; CB; RoHS, China and RoHS, WEEE
Warranty	3 years standard
MTBF	50,000 hours demonstrated
What's in the Box	QIG, Japan Class-B TM info sheet, User Manual CD, 50W Power Brick, power cable, IEC 60320-C13 to NA/EU plug, DVI-D cable, VGA cable (DB-15 male to DB-15 male), USB cable (Type A plug to Type B plug), audio cable, stand base assembly, filler plate

## Ordering Information

Model	Part Number	Technology	Surface Treatment	Interface	Color	Availability
1723L	E785229	IntelliTouch ZB Dual Touch	Antiglare	USB	Black	Worldwide
	E683457	TouchPro PCAP	Antiglare	USB	Black	Worldwide
	E016808	TouchPro PCAP	Antiglare	USB	White	Worldwide

## Optional Peripherals / Accessories

Part Number	Peripheral	Color
E628912	Magnetic stripe reader	Black
E000450	1723L VESA Mount Plate	Black
E000451	1723L VESA Mount Plate	White
E066148	PCAP Stylus Pen	Blue

## Extended Warranty Options

Part Number	Description
758588-000	1 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
930057-000	2 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
E67295-000	Elo advance unit replacement for touchmonitors

To find out more about our extensive range of Elo touch solutions, go to [elotouch.com](http://elotouch.com), or call the office nearest you.

### North America

Tel +1 408 597 8000  
 Fax +1 408 597 8050  
[elosales.na@elotouch.com](mailto:elosales.na@elotouch.com)

### Europe

Tel +32 (0)16 70 45 00  
 Fax +32 (0)16 70 45 49  
[EMEA.Sales@elotouch.com](mailto:EMEA.Sales@elotouch.com)

### Asia-Pacific

Tel +86 (21) 3329 1385  
 Fax +86 (21) 3329 1400  
[www.elotouch.com.cn](http://www.elotouch.com.cn)

### Latin America

Tel +52 55 2281 6958  
[elosales.latam@elotouch.com](mailto:elosales.latam@elotouch.com)

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, IntelliTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2018 Elo Touch Solutions, Inc. All rights reserved. 18091AES00057

