







5.7" screen & compact body

The EA510's vivid display will give you the most exciting visual experience. The 5.7" sized screen combined with a small body size will give an excellent ergonomic feeling.



Quick charge

Thanks to the Quick Charge 4.0 technology, you will spend less time charging - fully charged within 3 hours.



Fingerprint reader

Instantly unlock the EA510 with a slightest touch. The fingerprint reader is located on the back for easy access.













Removable battery

For the enterprise smartphone, long battery life is essential. The EA510 comes with a swappable 4300mAh battery - long time usage without any concerns.











Professional accessories

Boost the functionality of the EA510 device with Unitech's unique and versatile accessories. From single charging cradle to trigger gun grip to extended 5-slot charging cradles.

Enjoying every task - The EA510 is designed to look sleek, feel sleek and work sleek - ALL DAY ROUND!

This enterprise mobile computer offers all great enterprise features but styled into a consumer smartphone design. The EA510 is impressive with its large 5.7" screen and thin and lighter design. More power-efficient for full-shift usage plus running with Android 9.0 or Android 10 OS.

There is nothing more frustrating than when your device lags in the middle of a task. That's why the EA510 boosts a snappy processor: Qualcomm 660 Octa-core 64bits 2.2 GHz Processor.

The EA510's is a multitasking, responsive and ergonomic device whilst being competitively priced - it's time to move forward.





EN Version 1.7 EA510

Operation System

Qualcomm 660 Octa-core 64bits CPU

2.2 GHz Processor

Memory RAM: 4GB DDR4, ROM: 64GB

Android 9 with GMS OS

(Android 10 upgrade available)

Compatible through R

Micro SD/TF (max. 128GB) + Dual Nano-SIM Card Slot

Language Support Multiple languages supported

Display

5.7" (18:9) TFT-LCD HD colour (720 x 1440 pixels) display 1.1mm thick Corning Gorilla Glass III. Multi-touch and ultra sensitive capacitive touch screen, compatible with gloves and supports wet

resistance.

Camera/Photos/Video

Front: 5MP camera

Rear: 16MP camera, Auto Focus, LED flash light

Indicator

LED, speaker and vibration

Audio

Dual-microphone supports with noice cancellation, hight quality speaker, PTT headset support, cellular circuit switch voice, earphone

Communication

USB Type C (Host/Client) Interface

Expansion I/O Pogo Pin Yes, over USB Type C

OTG WLAN 2.4G/5G Dual frequency WIFI

IEEE 802.11a/b/g/n/ac/d/e/f/h/o/k/r/v/w

IPV4, IPV6,

Data rates

5Ghz: 802.11a/n/ac > up to 866.7Mbps 2.4Ghz: 802.11b/g/n/ > up to 300Mbps

Operation channels

2.4Gh: 1-13 (depends on regulatory rules &

certification agency

5Ghrz: 36,38,40,42,44,46,48,52,56,60,64,100, 104,108,112,116,120,124,128,132,136,140,149,

153,157,161,165.

Security and encryption

802.1x(EAP): EAP-TLS, EAP-TTLS, PEAP-MSCHAPv2, PEAP-TLS, PEAP-GTC,

PWD, SIM, AKA

Encryption: WEP, WPA / WPA2-PSK

2x2 MU-MIMO for faster uploading and

downloading speeds

Fast roaming PMKID caching, 802.11r, OKC Bluetooth 5.0 + BR/EDR + BLE with Bluetooth

up to 240* meters distance (*Depends on

environment and application). Increased range and bandwidth

Multiple devices connection supported Support Vo-LTE HD video voice call

Vo-LTE WWAN 4G LTE

MIMO

TD-LTE (B34/B38/B39/B40)

FDD-LTE (B1/B2/B3/B4/B5/B7/B8/B12/B19/B220/

B28A/B28B)

WCDMA (B1/B2/B4/B5/B8), TD-SCDMA (B34/B39),

CDMA2000 1xEV-DO Rev.A BC0 (800MHz),

CDMA 1x

GSM/EDGE/GPRS (850/900/1800/1900MHz)

4G data communication only version is also

available (no voice feature). GPS; GLONASS; Gallileo; and BeiDou and **GPS**

A-GPS

Other Sensors Acceleration sensor, Motion sensor, light

sensor, Proximity sensor & Gyroscope. 2Hz Random PK sine, 10cm displacement Vibration withstands multi-side 5000 vibration tests

Software Support















SOTI Team Viewer

Buttons

Side SCAN button x 2 (Left / Right), Power button, User-defined function button (programmable key), Volume switch button (+ / -), ON / OFF button, Touch keys x 3 (Home / Back / Recent)

Data capture

Scanning Scanner (Engine: N6703)

> Reads all major 1D and 2D codes Supports; multi-reading, Picklist reading,

Center decode, OCR function,

DOT code.

IFrequency 13.56Mhz (NXP NQ553) RFID/NFC/Mifare

ISO 14443 Type A&B; FeliCa/Mifare and ISO 15693; Reader mode P2P mode,

Card Emulation mode

Fingerprint reader

Chip-based sensor 112x88 sensing array

Support finger wake-up function One user enrollment per device

Power Source

Main battery Swappable and rechargeable 3.8V 4300mAh

Li-polymer battery pack.

Operation Typical operation Time 10 hours

(depending on the specific environment) Support QC4.0 with separate power adapter **Quick charging**

over USB type-C port only

Charging time <3 hours (supports QC4.0 quick charge)

Enclosure

250g (with battery) Weight

Dimension 162.6 mm x 76 mm x 13.6 mm

Environmental

Tumble

Operating temperature -20°C to 60°C -40°C to 70°C Storage temperature 0°C to 45°C Charging temperature

5% ~ 95% (non-condensing) Relative humidity Drop specification 1.5m drop to concrete at room

temperature per MIL-STD810G Tumble specification 1.0m tumbles

-40°C to 70°C rapid transition Terminal Shock

Sealing **IP67** ESD

±15kV air discharge ±8kV direct discharge

1.0m tumble for 200 cycles and

400 times

Regulatory Approvals CE, RED, RoHS, BQB



Unitech Europe

(Optional model)

Tilburg, The Netherlands • Tel.: +31 (0)13 460 9292 • Email: Info@eu.ute.com • Website: http://eu.ute.com