Epson TM-T88VI Series

DATASHEET / BROCHURE





Reliable, fast receipt printer with mobile connectivity, which makes it easy to add web and mobile POS services to a traditional PC-based POS system.

The TM-T88VI is Epson's new state-of-the-art receipt printer, designed to work with both traditional PC-based POS systems and increasingly popular web and tablet solutions. This makes it perfect for shop, bar and restaurant owners who want to develop effective new ways of interacting with customers, and also for those who just want to run a traditional or permanent combined system

Versatile

The versatile Epson TM-T88VI receipt printer offers retailers, restaurants, bars and other commercial businesses the chance to explore web and mobile POS solutions without losing the functionality of a traditional PC-based system, as both can be run in parallel. This co-existence means users can migrate at the speed they want, run both systems at once, or just stick to a traditional setup. **High performance and low running costs**

As well as flexibility, the TM-T88VI gives outstanding performance, with print speeds of up to 350mm/s, and excellent reliability. A backward paper-feeding function helps save paper without affecting performance, reducing running costs and paper waste.

Flexible connectivity

Server Direct Print functionality allows the TM-T88VI to print direct from a web server. It also supports beacons, to help mobile devices identify the nearest printer, making it ideal for POS environments with multiple printer installations, while NFC support makes it easy to pair tablets, smartphones and other mobile devices.

Compact desktop

The TM-T88VI has exactly the same footprint as the TM-T88V, allowing you to upgrade to a brand new system without having to rearrange your counter space, and is available in both black and white to suit any shop, bar or restaurant decor.

KEY FEATURES

- Fast print speeds Print at speeds of up to 350mm/s
- Proven reliability Epson's proven track record for reliability
- Co-existence Allows PC, mobile and web connection at the same time

• Server direct print Print directly from web server to any connected receipt printer

Beacon support

Lets mobile devices print to the nearest available printer



PRODUCT SPECIFICATIONS

FONTS & STYLES	
Column capacity	Paper width 80 mm, 58 / 80
PAPER	
Paper size	79.50 ± 0.50 (W) mm x dia 83.00 mm,
	57.50 ± 0.50 (W) mm x dia 83.00 mm
FONTS & STYLES	
Print Speed	350 mm/sec
Print Speed (default)	300 mm/sec
Printing Font	ANK
Column capacity receipt	Paper width 80 mm, 58 / 80
Character size	12 mm (W) x 24 mm (H) / 99 mm (W) x 24 mm (H)
Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic
Printing Characters	Text (incl. Euro symbol), Graphics, Barcode
INTERFACES	
Interfaces	USB 2.0 Type A, USB 2.0 Type B, Powered USB (optional), Parallel (optional), RS-232
	(optional), Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11b/g/n
	(optional), Wireless LAN IEEE 802.11a/b/g/n (optional), Drawer kick-out, Bluetooth (optional)
DATA BUFFER	
Data Buffer	4 kB or 45 Bytes
POWER	
Power Supply	PS-180, AC cable
Operating Voltage	24 V
5	
GENERAL	
Product dimensions	145 x 195 x 148 mm (Width x Depth x Height)
Product dimensions Product weight	1.6 kg
Product dimensions Product weight Colour	1.6 kg Black / White
Product dimensions Product weight Colour Installation	1.6 kg Black / White horizontally, wall hanging
Product dimensions Product weight Colour Installation Interface connectors	1.6 kg Black / White horizontally, wall hanging D.K.D. function
Product dimensions Product weight Colour Installation Interface connectors Supported Humidity	1.6 kg Black / White horizontally, wall hanging D.K.D. function Operation 10% - 90%
Product dimensions Product weight Colour Installation Interface connectors	1.6 kg Black / White horizontally, wall hanging D.K.D. function
Product dimensions Product weight Colour Installation Interface connectors Supported Humidity	1.6 kg Black / White horizontally, wall hanging D.K.D. function Operation 10% - 90%

Epson TM-T88VI Series

HAT'S IN THE BOX

- Connector Cover
- *Main unit*
- PS-180 & AC cable
- Paper spacer
- Power switch cover
- Roll paper
- Setup guide
- Varranty document

PTIONAL ACCESSORIES

- VH-10 (040) Wall hanging bracket C32C845040
- DT-BZ20-634: Optional External Buzzer C32C890634
- OT-WL02 (739): Wireless LAN Dongle, 2.4 GHz 0320890739
- DT-WL05 (737): Wireless LAN dongle, 2.4 and 5 ЗНz C32C890737

Co√erPlus

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00

Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

