

CITIZEN

Compact, feature-rich portable receipt printing

Compact. feature-rich portable receipt printing



CT-S280

POS, Receipt printer (thermal 2 inch / 58 mm)

Applications

- Healthcare
- Hospitality
- Journal
- Retail



Small but powerful

TOMORROW'S PRINTING TODAY

CITIZEN

Specifications

Model	CT-S280
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	80 mm/sec.
Print Width (maximum)	48 mm
Media Width (min to max)	57.5 mm (+/- 0,5 mm)
Media Thickness (min to max)	65 to 75 µm
Media Sensor	Paper end
Optional interfaces	Serial (RS-232C compliant), Parallel (IEEE 1284 compliant), USB
Power supply	100 to 240V, external power supply, Output: DC 8.5V
Reliability	100 Million pulses or 50 Km
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	106x170x116.5 mm, 0,43 Kg + 0,24 Kg Power supply
EMC and safety standards	CE, TUV, UL, C-UL, FCC class B, VCCI

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-S280

POS, Receipt printer (thermal 2 inch / 58 mm)

Features & Benefits

- Paper exit: Top exit - ideal for all retail applications
- Paper load: Easy paper loading
- Printing Speed: Prompt print out of receipts - up to 80mm per seconds



The ultra compact thermal printer for all kind of receipts and labels