



Kiosk Printer PMU3300

The high performance printer for heavy duty use.

Paper Width 58mm 80mm

Print Method Direct Thermal Printing

Functions Printing Speed: Up to 150mm/sec.

Applications



Receipts



Tickets

Features


Wide range of operating temperature:-15°C to 65°C

φ203mm big roll capability

Flexible paper roll positions



7 positions selectable for the paper roll

Left



Arm position: left or right


Right



Angle: 7 positions

Two types of paper holders

The small paper roll holder is not standard option.
Please contact us if you are interested.




Small paper roll holder



Big paper roll holder

High-lift mechanism

Easy media loading



Main Applications

Gas Station POS Equipment

Queue Management System

Printing from various data communication output terminals

KIOSK Terminal

Ticket Vending Machine

Specifications

Model Name	PMU3300
Print Method	Direct Thermal Dot Printing
Printing Width	3-inch = 72mm 2-inch = 48mm
Dot Density	8dots/mm(203dpi)
Paper	3-inch width= 80mm 2-inch width = 58/60mm
Maximum Printing Speed	150mm/sec.
Paper Feed Pitch	Minimum 0.125mm
Detection Functions	Head Temperature Detection Platen Presence Detection Paper End Detection
Drive Voltage	Input Voltage: DC24V±10%
Logic System Power Supply Voltage	DC24V±10%
Power Consumption	Approx. 1.9A (up to 9A)
Head Life	Pulse Resistance: 50 million pulses or more (12.5% print rate) Wear Resistance: 50km or more (room temperature, room humidity, specified recommended paper)
Operating Temperature/Humidity	Temperature: -15 to 65°C (printing guaranteed for 5 to 45°C), Humidity: 10 to 85% RH (no condensation)

