

PRINT & DISPENSING MODULES

Industrial OEM Print Modules to be integrated in various Print & Apply Solutions.

POWERFUL PRINT AND DISPENSING MODULES

As an engineering company or system integrator, you know your customers expect you to provide complete labeling devices tailored to their requirements. The Dispensing Print Modules (DPM) and Print Engine Modules (PEM) provide precise, safe printing and labeling for industries such as food, chemical and pharmaceutical and integrate seamlessly into most production lines.

DPM – Labels virtually any product with timed-to-the second precision, while processing variable data from label to label. Error-free product identification for use in logistics applications, individual packages in shipments or individual parts identification

- Flexible Printing and Dispensing
 - High performance, robust
 - Print and dispense wide range of labels
- Fast Printing and Dispensing in 1:1 Mode
 - Maximum print speed of 400 mm/s (24m/min)* and 300 dpi resolution
 - When a label is printed and dispensed, the DPM is preparing the data for the next label.
- Economic Solution
 - Increased uptime using 1000m ribbon rolls
 - Ribbon save function reduces consumable costs
- Available in RFID UHF mode

PEM – Extremely high printing speed make it suitable for identification of rapidly-moving products at variable conveyor speeds.

- Efficient Batch Printing
 - Printed labels are forwarded in a loop for further processing in a labeling machine or a rewinder
 - Definitive solution for variable product labeling at high dispensing speed

- Customizable Production Line Labeling
 - Can adapt to production line speed in various industry environments
 - Static products can be labeled with the same information over a specific time frame
 - Ideal for the food or pharmaceutical industry and where print speed is independent of the dispensing process
- Economic Solution
 - Increased uptime using 1000m ribbon rolls
 - Ribbon save function reduces consumable costs.

MORE INFORMATION

To learn more about our DPM and PEM Solutions please contact your NOVEXX Solutions representative or visit our website at www.novexx.com.



PRINT & DESPENSING MODULES

STANDARD FEATURES

PRINTSPEED

4"/5": 50mm - 400mm 6":50mm - 300mm

PRINT TECHNOLOGY

Thermal transfer/thermal direct

PRINTHEAD

300 dpi

PRINT WIDTH

4":106 mm 5":127 mm 6":160 mm

FONTS

Fonts including OCR-A and OCR-B, 3 scalable fonts, True Type fonts are supported; scalable in X/Y direction up to factor 16; rotation of internal character sets, bar codes, lines and graphics by 0, 90, 180, 270° for fix size fonts, 0°-359,9° for scalable fonts; TrueType fonts are infinitely rotatable.

BARCODES

1-dimensional: EAN 8 and EAN 13 with 2 and 5 digit add-on, UPC-A, UPCE, Code 39, Code 39 Ratio 3:1 and Ratio 2,5:1; Code ITF, Codabar, Code 128, Code 2/5, Code 2/5 1, Code 2/5 5, Code 2/5 Interleaved Ratio 1:3, Code 2/5 Matrix Ratio 1:2,5; Code 2/5 Matrix Ratio 1:3; Code MSI, Code EAN 128; Postcode (routing and ID code), UPS Code 128, Code 128 Pharmacy; all bar codes available in 30 widths and freely scalable in height; 2-dimensional: Data Matrix Code, Maxi Code, PDF 417, Codablock F, Code 49, QR Matrix code
GS1 databar and composite (CC) symbology

GRAPHIC FORMATS

BMP, PCX, JPG, TIF, GIF, Easy Plug logos

EMULATIONS

Easy Plug, line printer, Hex Dump, MLI

RFID

UHF (DPM only)

MEMORY

64 MB RAM

DISPLAY

Five-key control panel with illuminated graphical display; 128x32 dots, with two lines of 16 characters

CONSUMABLES

LABEL TYPES

All common converted, self-adhesive label material with liner, on rolls. Suitable for printing in thermal direct or thermal transfer process.

LABEL WIDTH (INCL. BACKING PAPER)

4"/5": 16 mm – 136 mm
6": 16 mm – 190 mm

RIBBON LENGTH

Up to 1000 m; max. roll diameter 110 mm

RIBBON WIDTH

Ribbon should overlap the label material some millimeters.

RIBBON SAVE FUNCTION

Standard

COMMUNICATIONS

DATA INTERFACES

Serial RS232 (optional RS422/485), 2x USB-A host, USB-B device, Ethernet 10/100 Base-T, Centronics, WLAN (by CF card)

SIGNAL INTERFACES

US1 I/O board (5V or 24V); 4 input/7 output I/O board D-sub 15 (providing signals similarsignal to US1) Applicator Interface board (optional for DPM).

PHYSICAL CHARACTERISTICS

OPERATING CONDITIONS

Temperature : 5 to 35°C; humidity : 45-75% non condensing

PROTECTION CLASS

IP 21

CERTIFICATIONS

CE, GS, TUV, NRTL (US/CA), GOST, FCC

OPTIONS

Various dispensing edges (DPM); RFID-UHF read/write module (DPM); 2nd RS232 option board; remote display; applicator interface board (DPM)

Novexx Solutions GmbH DEUTSCHLAND

Ohmstrasse 3
D-85386 Eching
Tel. +49 (0)8165 925 299
info.deutschland@novexx.com

Novexx Solutions S.A.S. FRANCE

Tel. +33 (0)825 82 61 52
info.france@novexx.com

Novexx Solutions B.V. NEDERLAND

Tel. +31 (0)30 760 90 10
info.nederland@novexx.com

Novexx Solutions B.V. BELGIE

Tel. +32 (0)2 377 8002
info.belgie@novexx.com

Novexx Etiketleme Sistemleri Tic. A.Ş. TÜRKIYE

Tel. +90 216 564 81 81
info.turkiye@novexx.com

Novexx Solutions GmbH ITALIA

Tel. +39 0331 1855511
info.italia@novexx.com

Novexx Solutions GmbH FILIAL SVERIGE

Tel. +46 (0)31 68 30 40
info.sverige@novexx.com

Novexx Solutions GmbH POLSKA

Tel. +48 (0)605957108
info.polska@novexx.com

manroland India Pvt. Ltd. INDIA

Tel. +91 (11) 47002900
info.india@novexx.com


Novexx Solutions USA

Tel. +1 610 4730751
info.usa@novexx.com

Novexx Solutions ASIA

Tel. +86 (021) 2215 7665
info.asia@novexx.com

DIRECT COMPARISON OF DPM AND PEM FEATURES AND BENEFITS



The information contained herein is believed to be reliable but NOVEXX Solutions makes no representations concerning the accuracy or correctness of the data. The information, like any other should be confirmed independently for the particular end user conditions to ensure the proposed labeling meets the relevant requirements and regulations. NOVEXX Solutions shall have no liability whatsoever, regardless of any legal theory, arising out of your use or reliance on the information contained herein and in no event shall NOVEXX Solutions be held liable for consequential, indirect or incidental damages. NOVEXX Solutions liability is limited to the replacement value of defective product. Products, information and specifications are subject to change without notice.

© 2016 NOVEXX Solutions GmbH, All Rights Reserved. Third party trademarks and/or trade names may be used herein are the property of their respective owner(s).