

RJ-3050

3" Mobile Printing Solution



Top Features:

Compatible with Windows®

- Print from Windows PC's through the USB interface or wirelessly

Ready to Integrate with iOS® & Android apps

- Using Brother SDK (3rd party development required)

Portable Durable Handheld Design

- Designed to withstand even the harshest conditions. 1.2m drop tested, IP54 rating.

Fast Print Speed

- Maximum 5ips (127mm/sec)(without peeler)

Low Maintenance costs

- Highly reliable direct thermal technology uses fewer moving parts than other printing technologies.

Low Consumable Costs

- No ink or ribbons to replace. The only consumable is the thermal media.

General

Carton contents	Belt Clip Li-ion battery (PA-BT-001-A) Documentation
Language support	UK, French, Dutch, German, Italian, Spanish

Dimensions & Weights

Without carton	113(w) x 186(d) x 80(h) 610g (including battery)
-----------------------	--

Built In Features

Printing Method	Thermal
Printing speed	Maximum 5ips (127mm/sec) (*Under Brother standard environment)
Maximum print width	72mm
Print resolution	203dpi
Number of sheets per battery charge	Li-ion battery: approx. 5300 labels (continuous print) *Under Brother standard environment)

Interfaces	USB Ver.2.0 (Full Speed) (mini-B). USB Host. Bluetooth Ver.2.1+EDR (Class 1. Wireless LAN IEEE802.11b/g/n (Infrastructure mode/Adhoc mode/Wireless Direct mode) IEEE802.11b/g/n (Infrastructure mode and Wireless direct mode:[b/g/n] / AdHoc mode:[b])
-------------------	--

Operating system support	Android 2.3 or later iOS 5 or later (requires 3 rd party app development using Brother SDK), information available at www.brother.eu/developer)
---------------------------------	--

Airprint support	TBC
-------------------------	-----

Printer commands	Raster ESC/P P-touchTemplate ZPL emulation CPCL emulation
-------------------------	---

Printer driver	Microsoft® Windows Vista® Windows® 7 / Windows® 8 Windows® 8.1 Microsoft® Windows Server® 2008 / 2008 R2 / 2012 / 2012 R2
-----------------------	---

Internal fonts & sizes	<ESC/P> Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size<16, 24, 32dot> Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot <P-touch Template> Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot
-----------------------------------	---

Supplies

RD roll type	RD-PO8E5(Receipt)
---------------------	-------------------

Optional Accessories

Batteries	Rechargeable Li-ion battery(PA-BT-001-B):7.2V Continuously Printing 5300 labels (*Under Brother standard environment)
Shoulder Strap	PA-SS-4000
AC adaptor	PA-CR-001 Single Cradle PA-BC-001 Single Battery Charger PA-AD-600 AC Adapter
Car adaptor	PA-CD-600CG Cigar lighter plug PA-CD-600WR Permanently wired