



## General purpose ribbon designed for fabric labels

### Key benefits

- Designed for intensive printing
- Resistant to textile cleaning processes
- Certified OEKO-TEX Standard 100 for maximum confidence on all textile applications

### Applications

- Garment labels
- Outdoor equipment labels
- Automotive interior labels



### Recommended substrates

Nylon taffeta	● ● ● ● ● ●
Satin polyester	● ● ● ● ● ●
Polyester taffeta	● ● ● ● ● ●

### Print quality

Barcode	● ● ● ● ● ●
Darkness	● ● ● ● ● ●
Small characters	● ● ● ● ● ●

### Print resistance

Washing	● ● ● ● ● ○
Dry cleaning	● ● ● ● ● ●
Ironing	● ● ● ● ● ○

### Printer parameters

Maximum speed: 8 ips (200 mm/s)

Heat settings:



### Technical specifications

Film thickness: 4,5µm  
 Total ribbon thickness: <8µm  
 Ink melting point: 75°C | 167°F  
 Coefficient of friction: Kd < 0,2  
 Ink blackness: 1,8 ODR  
 Antistatic designed

### Approvals

OEKO-TEX Standard 100 - Class I - CQ1172/1 IFTH  
 REACH / SVHC 1907/2006/EC  
 EU Food Contact 1935/2004/EC  
 RoHS / Heavy Metals 2011/65/EU  
 California Proposition 65  
 Halogens IEC 61249-2-21:2003

### Storage conditions

- 12 months recommended
- 20-80% Relative Humidity
- 5-35°C (40-95°F) temperature

### Colors

