LANDI

C20 Pro
ECR Terminal

Elevate user experience to new heights with futuristic terminal.

- Enhance user perception with interactive design.
- Tackle peak hours with seamless and speedy printing.
- Empowered by LANDI Connect platform to unlock the full potential of digital commerce.

| SPECIFICATIONS

Processor	Qualcomm Octa-core, 2.2GHz	**Connectivity**	Wi-Fi: IEEE802.11 a/b/g/n/ac 2.4G and 5G, Wi-Fi 6 ETH: 1000M Bluetooth 5.0, support BLE Optional, 4G fallback 3G and GPRS, WU、AM、CN
OS	Android 13		
Memory	Internal: 4GB RAM + 32GB FLASH 8GB RAM + 64GB FLASH (Optional) External: Micro SD Card (Up to 2TB)	**Positionning**	Optional, GPS, GLONASS, BEIDOU
		Audio	Speaker: 5W, 100dB@1m, Dual Speaker Headset: 3.5mm audio jack MIC: Dual Microphone
Main display	15.6",1920x1080,FHD capacitive multi-touch	**Camera**	Optional 1: None Optional 2: 0.3M pixels, QR code scan (Only supported on the 10.1'' Premium CFD) Optional 3: Facial recognition ability camera (USB device, plug into Main display edge expansion port)
Customer display	Optional 1: None Optional 2: 10.1" Standard CFD (1280x800 display only) Optional 3: 10.1" Premium CFD (1280x800, Touch panel, QR Camera, NFC) Optional 4: P30-T PCI payment tablet		
		NFC **(Optional)**	Android NFC, ISO / IEC 14443、 ISO15693 compliant, support Type A / B, Mifare， Felica (Only supported on the 10.1'' Premium CFD)
Printer	80mm Thermal Printer, Diameter : 80mm, Print speed: 200mm/s，Auto Cutter		
		SAM/SIM slots	1 SIM (Optional)
Ports	1*USB Type-C, debug port, 4*USB Type-A 2.0+1*USB Type-A 3.0, 1*RJ22 Serial port, 1*RJ45 Ethernet port, 1*RJ11 Cash drawer port, 1*3.5mm Audio port, 1*MicroSD slot, 1*Power port	**PSU**	19~20V/3.25A
		Environment	Operating temperature： -10℃ to +50℃ Storage temperature： -20℃ to +70℃ Operating humidity： 10% to 90% non-condensing
		Protection	Waterproof/Dustproof/Drop: IP41, 1.5m drop with packaging
Buttons	1 Power key with indicator light (Red&blue) 2 Volume keys	**Certification**	CE/CB/FCC/IC/RoHS/WEEE

LANDI