


Upgrade your experience with a combination of speed, convenience and portability

- Versatile mobile terminal powered by Android 13 for all mobile business needs.
- Supported by LANDI's asset management platform, **LANDI Connect**, to meet the evolving demands of today's digital world.
- Pocket-size design, enabling high-level productivity and connectivity on the go.



- Expansive 6.517 " touch screen and ergonomic interface
- Powerful processor for smooth operation (Qualcomm Quad-core CPU, 2.0GHz)
- Quick-swap battery on duty (3500mAh/7.7V)
- Advanced connectivity for high-mobility (2G/3G/4G, WiFi, GPS, Bluetooth 5.0, and optional eSIM)
- 5MP rear camera for convenient QR code reading Optional front camera



SPECIFICATIONS

Processor	64-bit ARM, Cortex Quad-core A53, 2.0GHz	Camera	Front camera: optional, 2M pixels, fixed focus camera, for code scanning Rear camera: 5M pixels, autofocus and flashlight
os	Android 13 (GMS Certified)		
Memory	3GB RAM + 32GB FLASH 4GB RAM + 32GB FLASH (Optional) MicroSD Card (Up to 2TB)	Card Reader	Optional, Android NFC, ISO/IEC 14443、 ISO15693 compliant, support Type A/B, Mifare, Felica
Display & Touchscreen	6.517'', IPS, 720X1600 HD capacitive multi-touch	SIM/SAM Slots	• 2 SIM + 2 SAM • eSIM (Optional)
Scanner	Option 1: NoneOption 2: LANDI Scan EngineOption 3: Honeywell Scan Engine	Connection	• 1 USB Type-C • 2 PIN Pogo Pin
	1 power key (Right side)	PSU	5V/2A
Buttons	2 scan code keys are located on each side (Optional)	Battery	3500mAh/7.7V, removable
Audio	2 volume keys (Left side) Speaker: 1W 90dB@0.1m Headset: USB Type-C MIC: Dual MIC	Accessories (Optional)	Terminal charging baseBattery charger (Support 4 batteries)Hand strap
Connectivity	Celluar: 4G fallback 3G and GPRS, Global band Wi-Fi: IEEE 802.11 a/b/g/n/ac 2.4G and 5G Bluetooth: Bluetooth 5.0, support BLE	Environment	Operating temperature: -10 ℃ to +50 ℃ Storage temperature: -20 ℃ to +70 ℃ Operating humidity: 10% to 90% non-condensing
Protection	1.2m drop tested *Data from LANDI Lab		
Positionning	Tracking GPS, GLONASS		
Sensor	G-sensor, support screen rotation automatic Light Sensor	Certification	CE/CB/FCC/IC/RoHS/WEEE/GMS

*When MicroSD card is inserted. Card slot is 1 SIM + 1 MicroSD + 2 SAM.



