# elo

## 1304LS 13-inch LCD

**Touchscreen Monitor** 





Optically-bonded display



Ultra-thin design



**Energy Star 8.0** certified

## **Product Overview**

The Elo 1304LS 13-inch Full HD touchscreen monitor delivers commercial-grade durability, brilliant display clarity with state-of-the-art optical bonding and a minimalistic design perfect for any application. Backed by a three-year warranty, the 1304LS offers an energy efficient TouchPro® PCAP touchscreen enabling up to 10 simultaneous touches. With a clean design aesthetic, dual built-in speakers, flexible mounting options and increased viewing comfort with low blue light, the 1304LS touchscreen is well-suited for POS, HMI, interactive digital signage and self-service.

Create a sleek POS terminal with the 1304LS and the Elo Pay 7" Integrated payment solution.

USB-C interface that provides touch, video and power connectivity

Durable IK07 design with chemicallystrengthened scratch resistant glass

Narrow border touchscreen with edge-to-edge glass

#### 1304LS 13-inch LCD Touchscreen Monitor

Specifications				
Color	Dark gray			
Diagonal Size	13.3" / 337.82 mm			
Active Touch Area	11.57" x 6.5" / 293.76 mm x 165.24 mm			
LCD Technology	Active matrix TFT LCD			
Touch Technology	TouchPro PCAP			
Number of Touches	10 Touches			
Aspect Ratio	16:9			
Native Resolution	1920 x 1080			
Preset Video Timings	640x480 60Hz, 800x500 60Hz, 800x600 60Hz, 1024x768 60Hz, 1280x800 60Hz, 1280x720 60Hz, 1280x1024 60Hz, 1366x768 60Hz, 60Hz RB, 1440x900 60Hz, 60Hz RB, 1680x1050 60Hz, 60Hz RB, 1920x1080 60Hz			
Number of Colors	16.2M			
Brightness (typical)	Panel: 300 nits; with TouchPro PCAP: 270 nits			
Response Time (Tr + Tf) (typical)	27 msec			
Viewing Angle (typical)	Horizontal: 89°/89° or 178° total; Vertical: 89°/89° or 178° total			
Contrast Ratio (typical)	600:1			
On-Screen Display (OSD)	Accessible through touch OSD, and press Menu button to pop up touch OSD diagram.  Controls: Menu, Power  Settings: Brightness, Contrast, Color Temperature, Low Blue Light, Volume, Mute, OSD Timeout, OSD Language, Sharpness, Touch on Sleep mode ON/OFF, Power LED ON/OFF, Recall Defaults  Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese  Lockouts: OSD, Power			
I/O Ports	USB Type-C connector			
Video	USB Type-C connector Input Video Horizontal Sync frequency range: 30 - 82KHz Input Video Vertical Sync (frame rate) frequency range: 60Hz			
Speakers	2 x 2W (+/-10%) internal speakers			
Power	Power Delivery compatible via USB Type-C connector ON (Default - 100% Brightness): 6.6W SLEEP: 0.8 W OFF: 0.15 W			
Dimensions with Stand (H x W x D)	Without VESA Adapter: 12.27" x 7.56" x 0.59" / 311.52 mm x 191.86 mm x 14.88 mm With VESA Adapter: 12.27" x 7.56" x 0.79" / 311.52 mm x 191.86 mm x 19.88 mm			
Shipping Dimensions	14.88" x 9.92" x 3.62" / 378 mm x 252 mm x 92 mm			
Weight	Unpackaged: 1.92 lbs / 0.87 kg Packaged: 3.42 lbs / 1.55 kg			
Mounting Options	VESA via 4-hole 75mm mounting adapter on rear of unit.			
Temperature	Operating: 0° C to 40° C / 32°F to 104°F; Storage: -20° C to 60° C / -4°F to 140°F			
Humidity (non-condensing)	Operating: 20% - 80% / Storage: 10% - 95% (38.7° C max wet bulb temperature)			
Regulatory approvals and declarations	Canada CUL, IC; Europe CE; Korea KCC; Taiwan BSMI; United States FCC, UL; Japan VCCI; International CB; Australia RCM; Mexico NOM; RoHS, Chir RoHS, WEEE, REACH; United Kingdom UKCA			
Impact Protection	IK07			
Other Features	Energy Star 8.0 TUV Rhineland (Low Blue Light) Power collection function via DDCCI			
Warranty	3 years			
MTBF	50,000 hours demonstrated			
Extended Warranty Option	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125			
Box Content 1304LS Touch monitor Quick Install Guide USB Type-C cable 75mm VESA adapter (assembled)				

### **Ordering Information**

Part Number	Technology	Surface Treatment	Touch Interface	Color
E968117	TouchPro PCAP	Anti-glare	USB	Dark Gray

Learn more about Elo at **EloTouch.com**.

Americas Europe (EMEA)

Tel +1 408 597 8000 Tel +32 16 930 136 elosales.na@elotouch.com EMEA.Sales@elotouch.com **Asia Pacific** 

Tel +86 (21) 3329 1385 Elo.Asia@elotouch.com



