

# C20 DS

Display System



\* Displayed accessories are for illustration only and are not sold separately.



Elevate Your Workspace with  
Precision and Durability.

- **Crystal-clear Visuals:** Enjoy sharp, immersive display with a 15.6" IPS touchscreen.
- **Built for Tough Environments:** IP55-rated for dust and water resistance, perfect for demanding spaces.
- **Seamless Integration:** Multiple I/O ports and Power over Ethernet (POE) support for versatile connectivity and simplified installation.
- **Convenient NFC Reader:** Integrated under-screen NFC reader for fast, contactless interaction, enhancing user convenience.



## SPECIFICATIONS

<b>Processor</b>	Quad-core 2.0GHz	<b>Certifications</b>	CE/CB/FCC/IC/WEEE/RoHS
<b>OS</b>	Android 13	<b>Ports</b>	1*USB Typec-C, debug port 4*USB Type-A 2.0,1*RJ22 Serial port, 1*RJ45 Ethernet port, 1*RJ11 Cash drawer port, 1*3.5mm Audio port,1*Micro SD slot 1*Power port
<b>Memory</b>	4GB RAM + 32GB FLASH MicroSD Card		
<b>Display</b>	15.6", IPS, FHD, 1920x1080 px capacitive multi-touch		
<b>Buttons</b>	1 Power key		
<b>Audio</b>	Speaker: 3W Speaker Headset: 3.5mm audio jack	<b>Cable management</b>	Water resistant cable cover
<b>Connectivity</b>	Wi-Fi: IEEE802.11 a/b/g/n 2.4G and 5G ETH: 1000M Bluetooth 5.0, support BLE	<b>Mounting</b>	75x75, 100x100 VESA mount
		<b>Protection</b>	IP55, dust and water resistant
<b>NFC</b>	Dual NFC reader under screen	<b>Power Supply</b>	Input: 100V~240V AC/50~60Hz/0.6A Output: 19V DC/2.1A
<b>Accessories</b>	LED alert system, 5MP Camera, MSR reader		
<b>POE</b>	Supports power over ethernet		
<b>Power on option</b>	Auto-boot switch	<b>Environment</b>	Operating Temperature: 0 C to +40 C Storage temperature: -20 C to +60 C Operating humidity: 10% to 90% non-condensing
<b>Net Weight</b>	1.8KG		
		<b>Dimensions</b>	361.5mm*233mm*35.7mm

**LAUDI**

This document is not binding and the specifications above can be modified without prior consent.

