

# MP72 Series Multi-Plane Scanner/Scale

# Redefine the checkout experience with unmatched speed and unrivaled innovation

In an age of endless shopping choices, customers expect to get in and out of stores quickly, with a choice of how they shop. Set a new standard for checkout convenience with the MP72 Series Multi-Plane Scanner/Scale.¹ As Zebra's latest bioptic scanner, the MP72 Series delivers the fastest checkout performance yet—with premium scanning speeds and an ease of use that ensures every customer enjoys a swift and seamless experience. Innovative features include an optional color camera that enables computer vision applications and helps minimize shrink, so you can optimize your workforce and provide customers with convenient self-checkout options without hurting your bottom line. A smart investment, the MP72 Series makes it easy and cost-effective to modernize your checkout with low energy consumption, superior uptime and easy integration with existing infrastructure.



# **Exceed Expectations with Faster-Than-Ever Checkouts**

## Premium scan performance from an industry leader

With a high-resolution megapixel sensor and Zebra's exclusive PRZM Intelligent Imaging technology, the MP72 Series offers unmatched scanning speed and simplicity on virtually any 1D, 2D, GS1 or Digimarc®, paper and mobile barcode. Poorly printed, damaged, crinkled or faded barcodes won't slow down your checkouts. Offset illumination makes it even easier to scan reflective barcodes on customer phones and glossy packaging.

### Future-ready with optimized 2D and Digital Link performance

As information-rich 2D barcodes like GS1 Digital Link become more prevalent at the POS, your customers still expect the easy swipe experience of 1D. New hardware and software advancements deliver significantly better 2D performance, helping ready your checkout lanes for the rise of 2D barcodes.

# Maximum checkout speeds with up to 2x larger fields of view

With high swipe speeds and fields of view that are up to 100% larger than other scanners in its class², the MP72 Series makes scanning second nature. There's less need to carefully position barcodes—providing a simpler experience for everyone, from experienced cashiers to first-time users.

# Innovative Features at Self-Checkout Drive Higher ROI and Reduce Shrink

## Optional color camera enables new vision-based applications

An optional HD color camera captures the smallest details, paving the way for new computer vision applications that enhance the customer experience and protect your bottom line. Produce recognition applications can help identify produce to streamline item selection for faster, easier checkouts. Loss prevention applications can identify suspicious transactions, ensuring the proper barcode is scanned for an item. And the presence of livestreaming video at self-checkout can discourage fraud.



### Ensure accurate weight measurements every time

The L-shaped platter design increases the active weighing surface area, making it easier to capture the full weight of large items. Zebra's Weight Guard intelligently senses whenever an item is not fully on the weighing surface and alerts the POS to take the steps necessary to prevent an underweight reading.

#### Fight loss with EAS support

Optional support for electronic article surveillance (EAS) systems gives your customers a seamless shopping experience—a single swipe deactivates the EAS tag and captures item price. Interlock eliminates the risk of "sweethearting" and other forms of shrink as the barcode must be scanned in order to deactivate the EAS tag.

#### Works with overhead cameras for loss prevention

The "good decode" LED is visible from front and top views, making it easy for users and self-checkout attendants to confirm that a scan was completed. Overhead cameras can utilize the LED for loss prevention—tracking a successful scan for every item placed in the bagging area.

## **Enhance Your Customer's Checkout Experience**

#### Eye-friendly intelligent illumination

Since the recessed illumination is practically invisible and dimmed when not scanning, the MP72 Series is easier on the eyes of cashiers and customers.

## Easy self-scanning with customer facing scanner

In cashier-assisted lanes, an optional customer facing scanner lets customers scan their mobile or paper coupons, loyalty cards, impulse buys and more.

## Add handheld scanners for in-cart scanning

Standard auxiliary ports can support a handheld scanner, so users can easily reach heavy or bulky items in the cart.

## Minimize exceptions for faster checkouts

Zebra's selectable label identifiers can convert one barcode type to another—for example convert a QR code to code 128—to eliminate exceptions and manual data entry that slow down transactions.

#### **A Smarter Investment**

#### Lowest power consumption in its class

With energy bills among the largest in-store operating expenses, it's critical to make your store as energy efficient as possible. Zebra's Intelligent Illumination system activates the LED lights only when merchandise is in the scan zone. The result? The MP72 Series uses up to 50% less power than other bioptic scanners.

#### Deploying made easy

With three standard sizes, the MP72 Series has the right solution to fit your store. It can drop right into an existing cash wrap, providing a cost-effective path to the latest POS technology. Multiple on-board interfaces ensure compatibility with all popular POS systems and auto-host detect cables simplify installation.

## Superior durability for maximum uptime

The MP72 Series is designed with over 50% fewer interconnects and PCBs than other multi-plane scanners—resulting in fewer failure points, fewer parts to repair and fewer things to go wrong. Solid state technology minimizes wear and tear to further lower breakdown and repair costs. A spill-proof design protects against inevitable spills and you can choose Sapphire or Diamond-Like Carbon (DLC) coating glass.

#### Easily serviceable

The MP72 Series is the least complex, most reliable and most easily serviceable scanner assembly in its class. And with Zebra's Remote Diagnostics, you can remotely monitor the status of illumination, sensors, cameras, scales, boards and more without having to travel onsite to diagnose a problem.

## Make data-driven decisions informed by your scanners

Zebra's IoT Connector, a fully automated real-time data collection tool, routes data from your scanners into your preferred IoT endpoint. You can mine the data and get the insights needed to make decisions in real time.

## Zebra DNA™—your scanner's built-in advantage

With more than 50 years of field-proven innovation, Zebra knows the scanning journey better than other providers. That's why we've developed Zebra DNA, a suite of software tools that make it easy to navigate your scanning journey. For example, 123Scan simplifies every step of deploying your scanners. With Advanced Data Formatting, you can easily create scanner data formatting rules to optimize your workflows and solve business problems. Powerful complimentary management software enables easy remote management. And much more.

# **Specifications**

| Physical Characteri                         |  |
|---|--|
| Dimensions                                  | Long scanner and scanner/scale: 20 in. L x 11.5 in. W x 4.00 in. D x 5.00 in H 506 mm L x 292 mm W x 101 mm D x 128 mm H Medium scanner and scanner/scale: 15.7 in. L x 11.5 in. W x 4.00 in. D x 5.00 in. H 398 mm L x 292 mm W x 101 mm D x 128 mm H Short scanner: 13.9 in. L x 11.5 in. W x 4.00 in. D x 5.00 in. H 351 mm L x 292 mm W x 101 mm D x 128 mm H  |
| Weight                                      | Long scanner: 13.10 lb/5.94 kg<br>Long scanner/scale: 17.85 lb/8.10 kg<br>Medium scanner: 11.20 lb/5.06 kg<br>Medium scanner/scale: 15.95 lb/7.22 kg<br>Short scanner: 11.55 lb/5.22 kg  |
| Scale                                       | 30 lb in 0.01 lb increments/15 kg in 5 g increments Maximum static weight: 300 lb/136 kg Single-cable and dual-cable protocols Compatible with Mettler price computational scale Options: 0-12 lb in 0.005 lb increments and 12-30 lb in 0.01 lb increments 0-6 kg in 2 g increments and 6-15 kg in 5 g increments Single-head and dual-head remote scale displays |
| Horizontal Glass                            | Sapphire and DLC coated; leek bar option for scale models  |
| User Indicators                             | Soft touch capacitive pads (no buttons to break or wear out) Good Decode LED (Front and Top) Speaker (adjustable tone and volume) Four programmable buttons  |
| Ports                                       | One shared POS port for USB/RS-232/IBM RS-485 Three USB peripheral ports Two powered RS-232 peripheral ports Checkpoint Interlock port Remote scale display port Color Camera USB 3 type-C   |
| Supported Host<br>Interfaces                | USB, RS232, IBM46XX over RS485, SNAPI  |
| Electronic Article<br>Surveillance          | Compatible with Checkpoint and Sensormatic EAS deactivation system   |
| Power                                       | 12VDC from POS interface cable (USB PlusPower)<br>Zebra PWR-BGA12V50W0WW power supply: 90-<br>264 V (110-240 nominal), 47-63Hz (50-60 nominal)<br>Idle Mode: 2.0 W (typical)<br>Active Mode: 2.75 W (typical)  |
| User Environment                            |  |
| Operating Temperature                       | 32.0° F to 104.0° F/0.0° C to 40.0° C  |
| Storage Temperature                         | -40.0° F to 158.0° F/-40.0° C to 70.0° C   |
| Humidity                                    | 20% to 95%, non-condensing   |
| Environmental Sealing                       | IP5X   |
| Ambient Light<br>Immunity (for<br>scanning) | Artificial Light: 0—450 Foot Candles (4,842 LUX)<br>Sunlight: 0—8,000 Foot Candles (86,080 LUX)  |
| Imaging Technology                          | <b>/</b>   |
| Туре  | CMOS Array Imager  |
| Illumination                                | Intelligent illumination   |
| manimation                                  | ,  |

| Color Camera                        |  |
|-------------------------------------|--|
| Resolution                          | HD Camera  |
| Interface                           | Industry standard USB 3 Type-C   |
| Orientation                         | Landscape, upper (facing down) or lower (facing up)  |
| Graphic Format                      | Bitmap, JPEG, RAW  |
| Illumination                        | White LED  |
| Symbol Decode Cap                   | pability   |
| 1D                                  | All major 1D barcodes including Code 39, Code 128,<br>Code 93, Codabar/NW7, Code 11, MSI Plessey, UPC/<br>EAN, I 2 of 5, Korean 3 of 5, GS1 DataBar, Base 32<br>(Italian Pharma)   |
| 2D                                  | All major 2D barcodes including PDF417, Micro<br>PDF417, Composite Codes, TLC-39, Aztec,<br>DataMatrix, MaxiCode, QR Code, Micro QR, Han<br>Xin, Postal Codes, SecurPharm and future GS1<br>Digital Link barcodes  |
| Digimarc                            | Digimarc barcodes  |
| Minimum Input<br>Resolution         | Code 39: 3.0 mil; Code 128: 3.0 mil; DataMatrix: 5.0 mil; QR Code: 5.0 mil   |
| Refer to Product Reference          | e Guide for complete list of symbologies.  |
| Accessories                         |  |
| Customer Facing Scanner,            | Pole Displays, Single and Dual Head  |
| Regulatory                          |  |
| Environmental                       | EN IEC 63000:2018  |
| Electrical Safety                   | UL 62368-1; CAN/CSA-C22.2 No. 62368-1-14; IEC 62368-1; EN 62368-1  |
| LED Safety                          | IEC 62471; EN 62471  |
| EMI/RFI                             | 47 CFR Part 15, Subpart B, Class B; ICES-003<br>Issue 7, Class B; EN55032, EN55024, EN55035;<br>EN61000-3-2; EN61000-3-3   |
| Utilities and Manag                 | ement  |
| 123Scan                             | Programs scanner parameters, upgrades firmware, displays scanned barcode data, scanning statistics, battery health, asset data and prints reports. www.zebra.com/123scan   |
| Scanner SDK                         | Generates a fully-featured scanner application, including documentation, drivers, test utilities and sample source code.  www.zebra.com/scannersdkforwindows   |
| Scanner Management<br>Service (SMS) | Remotely manages your Zebra scanner and queries its asset information. www.zebra.com/sms   |
| Loss Prevention                     | EAS Checkpoint supported Checkpoint Interlock via optional cable Sensormatic supported Color camera for image/video transfer or live streaming (optional) Front and top "Good Decode" LED Zebra Scale Platter: Integrated horizontal and vertical platter for increased weighing area Zebra Weight Guard |

## Markets and **Applications**

## Retail

- Grocery
- Supermarkets/ hypermarkets
- Mass merchandisers
- Discount chains
- Warehouse clubs
- Pharmacies
- Self-checkout systems in any retailer

#### **Applications**

- Point of sale (manned and self-checkout)
- Paper and mobile barcodes
- Produce identification
- Loss prevention
- Age verification
- EAS
- Loyalty applications
- Vision-based applications

#### PRODUCT SPEC SHEET

#### MP72 SERIES MULTI-PLANE SCANNER/SCALE

#### Warranty

Subject to the terms of Zebra's hardware warranty statement, the MP72 Series, is warranted against defects in workmanship and materials for a period of One Year from the date of shipment. Complete Zebra hardware product warranty statement: www.zebra.com/warranty

#### **Recommended Services**

Zebra OneCare™ Select; Zebra OneCare Essential

#### **Footnotes**

- 1. MP72 Series and accessories available Q2 2024
- 2. Depending on barcode location
- Specifications are subject to change without notice.

#### Zebra DNA

Zebra DNA is a suite of highly intelligent firmware, software, utilities and apps exclusively engineered to add functionality and simplify the deployment and management of Zebra scanners. For more information about Zebra DNA and its applications, please visit www.zebra.com/datacapturedna























