



FH190

Impact panel printer for industrial use

- Impact printing technology with dot matrix (8 pin)
- Paper width: 58mm
- Roll diameter: 50 mm
- Printing > 30 mm/sec
- RS232 interface
- Characters: European, International, Portuguese and Nordic
- Sensors: paper end
- Dimensions (LxWxH): 119x119x45.5mm
- Weight: 362 g (without paper roll)

CHARACTERISTICS

- Easy installation and universal mounting with panels of different thickness
- When the front panel opens up, all the mechanical parts are positioned in such a way as to make paper loading easier

APPLICATIONS:

- Measurement instruments
- Weighing systems
- Alarm systems
- Gas analyzers

AVAILABLE VERSIONS:

- FH190 24 RS232 5 Volt RTCK
- FH190 24 RS232 9/40 Volt RTCK
- FH190 40 RS232 5 Volt RTCK
- FH190 40 RS232 9/40 Volt RTCK

TECHNICAL SHEET

Printing Method	Dots impact matrix (8 pin)
Columns	24/40
Resolution	0.33 x 0.38 (24 columns); 0.19 x 0.38 (40 columns)
Printing (mm/sec)	67 cps
Character set	Normal and expanded
Printing Format	Normal, double height and width, bold
Printing Direction	Straight, 180°
Paper width	57 mm ÷ 0.5 mm
Roll Dimension	Ø 50 mm max
Emulation	Custom
Interfaces	RS232, Centronics
Data Buffer	1 KB
Flash Memory	64 KB
Software Tools	FontMake, LogoMake, UpgCePrn
Power supply	5 Vdc ± 10% (available 9÷40Vdc)
Medium consumption	2A
MTBF	260.000 hours (electronic board)
Head Life	50 Km/100M pulses
Operating temperature	0°C + 50°C
Dimensions	119x119x45.5mm
Weight	362 g

MODELS



915AF010100133
PRINTER FH190 RS232 24COL
RTCK



915AF010200133
PRINTER FH190 RS232 24COL
RTCK 9-40



915AF010300133
PRINTER FH190 RS232 40COL
RTCK



915AF010400133
PRINTER FH190 RS232 40COL
RTCK 9-40

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 09 January 2020