

FARGO® HDP8500



	FEATURES
Dual Sided Brinting	
Dual-Sided Printing	Standard 3 years***
Printer Warranty Printhead Warranty	Lifetime***
Printhead Warranty	PERFORMANCE STANDARDS
Puint Passivalian	
Print Resolution Cards per Shift	300 DPI Up to 1000/8-hour shift
•	Up to 150 cph / 24 seconds per card
Single-side YMC* Print Speed Single-side YMCK* Print Speed	Up to 124 cph / 29 seconds per card
Dual-side YMCKK* Print Speed	Up to 90 cph / 40 seconds per card
Multiple Print Mode Selection	Yes
Simultaneous Printing / Encoding	Yes
Memory	32MB RAM
Hemory	SECURITY STANDARDS
Printer Password Protection	Yes (Workbench and display)
Locking Card Input Hopper	Yes
Locking Card Output Hopper	Yes
Lockable Printer and Laminator Housing	Yes
Security Resin Erase	Yes (Standard)
Network Data Encryption	Yes
Trotheric Data Elleryphon	COMMUNICATION STANDARDS
Interface	USB 2.0 & Ethernet standard
One-Wire USB Encoding	
	Standard
Internal Ethernet Server	Standard Standard
Supported Software Drivers	Windows® XP / Server 2003 / Vista (32 & 64 bit) / Server 2008 R2 (64 bit) / Windows® 7 (32 & 64 bit)
T	USER INTERFACE STANDARDS
Touch Screen Display	3.2" display for status and help information
	ENVIRONMENTAL STANDARDS
Dual-Cooling Fans	Yes
Replaceable Fan Filter	Yes
Could brook Compaign (2 Homeses)	CARD STANDARDS
Card Input Capacity (2 Hoppers)	400
Dual Input Hopper Capability	Yes 200
Card Output Capacity (1 Hopper) Card Thickness	30-50 mil
Card Exception Feed	Yes
Card Cleaning Station	Two
Cara Cleaning Station	
Cartridge Loadable Pibbons	RIBBON STANDARDS
Cartridge Loadable Ribbons	RIBBON STANDARDS Yes
Fluorescing/UV Ribbon	RIBBON STANDARDS Yes Yes
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll)	RIBBON STANDARDS Yes Yes 750
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll)	RIBBON STANDARDS Yes Yes 750 500
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll)	RIBBON STANDARDS Yes Yes 750 500 500 500
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll)	RIBBON STANDARDS Yes Yes 750 500 500 500 1500 1500
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll)	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only)	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D Dual-sided only: 61 lbs / 27.7 kg
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only)	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D Dual-sided only: 61 lbs / 27.7 kg Yes Yes
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D Dual-sided only: 61 lbs / 27.7 kg Yes
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure Fully Accessible Card Path	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D Dual-sided only: 61 lbs / 27.7 kg Yes Yes Yes OPTIONS
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure Fully Accessible Card Path Dual-Sided Simultaneous Lamination**	RIBBON STANDARDS Yes Yes Yes 750 500 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D Dual-sided only: 61 lbs / 27.7 kg Yes Yes OPTIONS Yes
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure Fully Accessible Card Path Dual-Sided Simultaneous Lamination** Andon Production Status Light**	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D Dual-sided only: 61 lbs / 27.7 kg Yes Yes OPTIONS Yes Yes Yes
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure Fully Accessible Card Path Dual-Sided Simultaneous Lamination** Andon Production Status Light** ISO Card Flattener	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D Dual-sided only: 61 lbs / 27.7 kg Yes Yes OPTIONS Yes Yes Yes Yes Yes Yes Yes Ye
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure Fully Accessible Card Path Dual-Sided Simultaneous Lamination** Andon Production Status Light** ISO Card Flattener Embedded iCLASS SE* Encoder**	RIBBON STANDARDS Yes Yes 750 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D Dual-sided only: 61 lbs / 27.7 kg Yes Yes Yes OPTIONS Yes Yes Yes Yes Yes Yes Yes Ye
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure Fully Accessible Card Path Dual-Sided Simultaneous Lamination** Andon Production Status Light** ISO Card Flattener Embedded iCLASS SE* Encoder** Wi-Fi* Module**	RIBBON STANDARDS Yes Yes 750 500 500 500 1500 PHYSICAL CHARACTERISTICS 15.5" H x 28.2" W x 14.0" D Dual-sided only: 61 lbs / 27.7 kg Yes Yes Yes Yes Yes Yes Yes Ye
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure Fully Accessible Card Path Dual-Sided Simultaneous Lamination** Andon Production Status Light** ISO Card Flattener Embedded iCLASS SE* Encoder** Wi-Fi* Module** ISO Magnetic Encoding**	RIBBON STANDARDS Yes Yes Yes 750 500 500 500 500 1500
Fluorescing/UV Ribbon Full-Color - YMC* (maximum images per roll) Full-Color - YMCK* (maximum images per roll) Full-Color - YMCKK* (maximum images per roll) Retransfer Film (maximum images per roll) Dimensions Weight (printer only) Heavy Duty Metal Enclosure Fully Accessible Card Path Dual-Sided Simultaneous Lamination** Andon Production Status Light** ISO Card Flattener Embedded iCLASS SE* Encoder** Wi-Fi* Module** ISO Magnetic Encoding** Contact Smart Card Encoding**	RIBBON STANDARDS Yes Yes Yes 750 500 500 500 500 500 500 600

North America: +1 512 776 9000 Toll Free: 1800 237 7769 Europe, Middle East, Africa: +44 1440 714 850 Asia Pacific: +852 3160 9800

Latin America: +52 55 9171 1108

^{*} Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, I=Inhibit
** Option available from factory or as a field upgrade
**Three-year warranty available on printers and lifetime warranty available on printer with completion of online printer registration.
(Two-year warranty standard on both printer and printheads without online printer registration.)

hidglobal.com